

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-7-37

Relating to Certification of New Heavy-Duty
Off-Road Equipment Engines

DETROIT DIESEL CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

Pursuant to the December 15, 1998 Settlement Agreement between the Air Resources Board and Detroit Diesel Corporation and any modifications to the Settlement Agreement;

IT IS ORDERED AND RESOLVED: That the following Detroit Diesel Corporation 1999 model-year engines with rated power between 175 and 750 horsepower and exhaust emission control systems are certified as described below in heavy-duty off-road equipment:

Typical Equipment Usage: Pump, Compressor, and Generator Set

Fuel Type: Diesel

<u>Engine Family</u>	<u>Displacement</u>		<u>Exhaust Emission Control Systems and Special Features</u>
	<u>Liters</u>	<u>Cubic Inches</u>	
XDDXL12.1TFE (8V-92TA DDEC)	12.1	738	Charge Air Cooler Turbocharger Electronic Control Module

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), oxides of nitrogen (NOx), and particulate matter (PM) certification exhaust emission standards in grams per brake horsepower-hour (g/bhp-hr), and the opacity-of-smoke emission standards in percent (%) during acceleration (Accel), lugging (Lug), and peak (Peak) modes for this engine family are as follows (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx, and PM exhaust emissions certification values in grams per brake horsepower-hour, and the opacity-of-smoke emissions certification values in percent for this engine family are:

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity (%)</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
0.4	2.4	6.6	0.24	14	4	30

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel-Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.


BE IT FURTHER RESOLVED: That for the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Sections 2425 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

1. The Settlement Agreement is in effect.
2. The Settlement Agreement has not become null and void under Settlement Agreement Paragraph 165.
3. Detroit Diesel Corp. is in compliance with all applicable certification requirements of the Settlement Agreement.

Engines certified under this Executive Order must conform to all applicable California emission regulations and to all applicable terms and conditions of the Settlement Agreement.

Executed at El Monte, California this 16th day of January 1999.


R. B. Summerfield, Chief
Mobile Source Operations Division

A15

LARGE ENGINE MODEL SUMMARYManufacturer: **Detroit Diesel Corporation**Process Code: **New Submission**EPA Engine Family: **XDDXL12.1TFE**Manufacturer Family Name: **8V-92TA DDEC**

Engine Code	Engine Model	BHP@RPM (SAE Gross)	Fuel Rate: mm/stroke @ peak HP (for diesel only)	Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	Torque @ RPM (SEA Gross)	Fuel Rate: mm/stroke@peak torque	Fuel Rate: (lbs/hr)@peak torque	Emission Control Device Per SAE J1930
1A	8V-92TA DDEC	710 @ 2300	138.9	283.3	1770 @ 1500	148.3	197.3	ECM, TC, CAC
2A	8V-92TA DDEC	585 @ 2300	115.0	233.0	1594 @ 1350	123.0	151.0	ECM, TC, CAC
3A	8V-92TA DDEC	540 @ 2300	105.0	213.0	1454 @ 1350	112.0	137.0	ECM, TC, CAC
1B	8V-92TA DDEC	500 @ 2100	102.5	188.5	1500 @ 1300	118.7	140.0	ECM, TC, CAC
1C	8V-92TA DDEC	475 @ 2100	97.3	173.4	1425 @ 1200	117.6	119.8	ECM, TC, CAC
2C	8V-92TA DDEC	441 @ 1800	99.8	157.4	1425 @ 1200	113.1	118.4	ECM, TC, CAC
1D	8V-92TA DDEC	400 @ 2100	83.1	154.8	1150 @ 1200	88.8	93.4	ECM, TC, CAC
1E	8V-92TA DDEC	350 @ 2100	75.0	135.5	965 @ 1600	77.0	111.7	ECM, TC, CAC
1F	8V-92TA DDEC	365 @ 1800	84.9	134.0	1175 @ 1350	91.2	108.6	ECM, TC, CAC
1H	8V-92TA DDEC	300 @ 1800	70.9	112.5	965 @ 1350	75.5	89.8	ECM, TC, CAC
1J	8V-92TA DDEC	450 @ 1950	95.2	163.8	1469 @ 1200	111.4	120.0	ECM, TC, CAC
1K	8V-92TA DDEC	585 @ 2300	115.0	233.0	1725 @ 1500	139.2	185.2	ECM, TC, CAC
2K	8V-92TA DDEC	540 @ 2300	105.7	215.6	1475 @ 1350	116.1	139.0	ECM, TC, CAC
1L	8V-92TA DDEC	460 @ 1800	109.5	174.8	1400 @ 1350	108.0	129.3	ECM, TC, CAC
GS1	8V-92TA DDEC	568 @ 1800	137.8	217.9	NA	NA	NA	ECM, TC, CAC
GS2	8V-92TA DDEC	515 @ 1800	120.8	189.1	NA	NA	NA	ECM, TC, CAC
GS3	8V-92TA DDEC	365 @ 1800	85.7	135.5	NA	NA	NA	ECM, TC, CAC

EO# 0-8-7-37